





Barb (hose) connection with Rotary function

Model	Hose ID	A	φC	φD	φF	H	Weight(g)
22-SOHR	1/4	76	9	25	5	19	98
23-SOHR	3/8	76	11.3	25	7.5	19	98
24-SOHR	1/2	79	15	25	9	19	109




Nut Connection (For polyurethane Hose) with Rotary function

Model	Hose Size	A	φD	φF	H1	H2	Weight(g)
50-SOR	5.0×8.0	69	25	4	19	14	104
65-SOR	6.5×10.0	71	25	5.7	19	16	108
70-SOR	7.0×10.5	71	25	5.7	19	16	108
80-SOR	8.0×12.0	74	25	6.5	19	19	122
85-SOR	8.5×12.5	74	25	6.5	19	19	122
110-SOR	11.0×16.0	83	25	9.5	21	23	164



Nut Connection (For polyurethane Hose) with Rotary function & Sleeve Lock

Model	Hose Size	A	φD	φF	H1	H2	Weight(g)
50-SOL	5.0×8.0	69	25	4	19	14	104
65-SOL	6.5×10.0	71	25	5.7	19	16	108
70-SOL	7.0×10.5	71	25	5.7	19	16	108
80-SOL	8.0×12.0	74	25	6.5	19	19	122
85-SOL	8.5×12.5	74	25	6.5	19	19	122
110-SOL	11.0×16.0	83	25	9.5	21	23	164




One touch Socket with Rubber Covered Sleeve

ข้อต่อสวมเร็วและปลั๊กคุณภาพสูงที่มีลวดลายกันกระแทก สำหรับงานผลิตที่ต้องการการปกป้อง




Male Thread Socket

Model	Thread	A	φD	φF	H	Weight(g)
G22-SOM	R1/4	58	30	7.5	19	85
G23-SOM	R3/8	59	30	8	19	95
G24-SOM	R1/2	59	30	13	21	100



Female Thread Socket


Model	Thread	A	φD	H	Weight(g)
G22-SOF	Rc1/4	54	30	19	90
G23-SOF	Rc3/8	58	30	21	102
G24-SOF	Rc1/2	59	30	26	121






Barb (hose) connection Socket

Model	Hose ID	A	φ C	φ D	φ F	H	Weight(g)
G22-SOH	1/4	75	9	30	5	19	87
G23-SOH	3/8	79	11.3	30	7.5	21	91
G24-SOH	1/2	79	15	30	9	26	103




Nut Connection (For polyurethane Hose) Socket

Model	Hose Size	A	φ D	φ F	H1	H2	Weight(g)
G50-SOC	5.0×8.0	29	30	4	19	14	90
G65-SOC	6.5×10.0	61	30	5.7	19	16	94
G70-SOC	7.0×10.5	61	30	5.7	19	19	94
G80-SOC	8.0×12.0	61	30	6.5	19	19	108
G85-SOC	8.5×12.5	64	30	6.5	19	19	108
G110-SOC	11.0×16.0	69	30	9.5	21	23	139



Barb (hose) connection Socket with Rotary function

Model	Hose ID	A	φ C	φ D	φ F	H	Weight(g)
G22-SOHR	1/4	76	9	30	5	19	102
G23-SOHR	3/8	76	11.3	30	7.5	19	102
G24-SOHR	1/2	79	15	30	9	19	113



Nut Connection Socket (For polyurethane Hose) with Rotary function

Model	Hose Size	A	φ D	φ F	H1	H2	Weight(g)
G50-SOL	5.0×8.0	69	30	4	19	14	108
G65-SOL	6.5×10.0	71	30	5.7	19	16	112
G70-SOL	7.0×10.5	71	30	5.7	19	16	112
G80-SOL	8.0×12.0	74	30	6.5	19	19	126
G85-SOL	8.5×12.5	74	30	6.5	19	19	126
G110-SOL	11.0×16.0	83	30	9.5	21	23	168

