Free Angle type

ข้อต่อสวมเร็วคุรภาพสูง แบบทำงานอัตโนมัติสำหรับงานทั่วไป ผลิตจากวัสดุคุณภาพสูงด้วยเครื่องจักรที่ทันสมัยและควบคุมคุณภาพการผลิตจากประเทศญี่ปุ่น

Nut Socket

Model	Hose	A	ϕD	ϕF	H1	H2	Weight(g)
FSA-65CS	6.5×10.0	84.5	18.7	5.7	17	17	60

Female Plug

Model	Thread(T)	A	ϕE	H	Weight(g)
FJA-G2FP	G1/4	59	6	19	45

Hight Pressure Air Coupling

Use with Air tools with 3.0 Mpa air pressure

ข้อต่อสวมเร็วและปลั๊ก ขนาดเล็กเพื่อการใช้งานในพื้นที่จำกัด

This coupling was designed for the high pressure air tools such as the nailer with 3.0Mpa air compressors. It is getting more standard tools in the building industry. We have been supplying this kind coupling for major tool manufactures as OEM base. Now, we offer this series as standard products range.



Body Material	Steel with chrome plated
Max. Pressure	3.0MPa
Burst Pressure	4.0MPa
Sealing material	NBR
Temperature range in use	−20℃ ~ +80℃

Male Thread Socket

Model	Thread(T)	A	ϕD	ϕF	H	Weight(g)
30K-SOM	R1/4(LH)	56	26	5	19	99
G30K-SOM	R1/4(LH)	56	30	5	19	102

The picture is showing the socket with Robber protector.
It has "G" suffix on the top of modeling.



Female Thread

Model	Thread(T)	A	D	ϕF	H	Weight(g)
30K-PM	R1/4(LH)	40.7	2	5	14	30